

# GENESIS™

## TUBE SEALERS



**RAPID SEAL II™**  
**SE640**  
PORTABLE UNIT



**RAPID SEAL II™**  
**SE530**  
MULTI-HEAD SEALER



**RAPID SEAL II™**  
**SE540**  
SPACE SAVING BENCHTOP SEALER



**RAPID SEAL II™**  
**SE330 & SE340**  
STANDARD BENCHTOP UNIT

## Component processing is too important to leave to chance.

### SPEED

- No warm-up required – Instant on
- Rapid Seal II Technology
- Never overheat
- Notched Seal™ for easy separation

### COMPATIBILITY & RELIABILITY

- “Intelligent” RF Board – accepts and adjusts to all size blood tubing
- Legendary Genesis brand quality
- Trusted by blood banks worldwide
- 1 year warranty on parts and labor
- CE and UL compliant


### VERSATILITY & SAFETY

- Standard bench-top units
- Portable units (AC/Battery)
- Space saving units
- Flexible multi-head solutions

# GENESIS™ TUBE SEALERS

## WITH RAPID SEAL II TECHNOLOGY



Model	SE330	SE340	SE370	SE530	SE540	SE640	
<b>General Description</b>	<b>STANDARD BENCHTOP SEALER</b>	<b>MULTIPLE STATION BENCHTOP SEALER</b>	<b>BATTERY POWERED BENCHTOP SEALER</b>	<b>SPACE SAVING BENCHTOP SEALER</b>	<b>SPACE SAVING BENCHTOP SEALER</b>	<b>PORTABLE SEALING UNIT</b>	
<b>Sealing Head Configuration</b>	Fixed sealing head	Fixed and Hand-held sealing unit	Fixed and Hand-held sealing unit	Fixed sealing head	Fixed and Hand-held sealing unit	Hand-held sealing unit	
<b>Catalog #</b>	428-SE330	428-SE340	428-SE370	428-SE530	428-SE540	428-SE640	
<b>Special Features</b>	<ul style="list-style-type: none"> <li>Retractable splash guard</li> <li>"Intelligent" RF Board</li> <li>RAPID SEAL II seals in 0.5 to 1.2 seconds</li> <li>Easy Clean head protector</li> </ul>	<ul style="list-style-type: none"> <li>Retractable splash guard</li> <li>6' standard cable</li> <li>"Intelligent" RF Board</li> <li>RAPID SEAL II seals in 0.5 to 1.2 seconds</li> <li>Easy Clean head protector</li> <li>Use fixed and hand-held sealing unit independently</li> </ul>	<ul style="list-style-type: none"> <li>Retractable splash guard</li> <li>6' standard cable</li> <li>"Intelligent" RF Board</li> <li>RAPID SEAL II seals in 0.5 to 1.2 seconds</li> <li>Battery Operated and rechargeable</li> <li>Easy Clean head protector</li> <li>2000+ Seals per full battery charge</li> <li>Aluminum carrying case</li> </ul>	<ul style="list-style-type: none"> <li>Flexible multi-head option</li> <li>Splash guard</li> <li>"Intelligent" RF Board</li> <li>RAPID SEAL II seals in 0.5 to 1.2 seconds</li> <li>Custom Sealer Stand</li> <li>Easy Clean head protector</li> <li>Slim design to maximize available space</li> <li>Flexible Head Spacing (75 / 80 / 85 / 90 mm)</li> </ul>	<ul style="list-style-type: none"> <li>Flexible multi-head option</li> <li>Splash guard</li> <li>"Intelligent" RF Board</li> <li>6' standard cable</li> <li>RAPID SEAL II seals in 0.5 to 1.2 seconds</li> <li>Custom sealer stand</li> <li>Easy Clean head protector</li> <li>Slim design to maximize available space</li> <li>Flexible Head Spacing (75 / 80 / 85 / 90 mm)</li> </ul>	<ul style="list-style-type: none"> <li>6' standard cable</li> <li>RAPID SEAL II seals in 0.5 to 1.2 seconds</li> <li>Hand Sealing Unit</li> <li>Battery operated and rechargeable</li> <li>Lightweight canvas carrying bag included</li> <li>Medical device classified*</li> <li>1000+ Seals per full battery charge</li> </ul>	
<b>DIMENSIONS</b>	<b>Main Unit</b> <small>Inches mm</small>	6.9W x 6.1H x 13D 176W x 156H x 331D	6.9W x 6.1H x 13D 176W x 156H x 331D	6.9W x 6.1H x 13D 176W x 156H x 331D	2.9W x 9.7H x 12.8D 74W x 248H x 326D	2.9W x 9.7H x 12.8D 74W x 248H x 326D	6.1W x 1.5H x 14.4D 156W x 37H x 265D
	<b>Hand Held Sealing Unit</b> <small>Inches mm</small>	N/A	1.1W x 1.8H x 8.1D 28W x 44H x 204D	1.1W x 1.8H x 8.1D 28W x 44H x 204D	N/A	1.1W x 1.8H x 8.1D 28W x 44H x 204D	1.1W x 1.8H x 8.1D 28W x 44H x 204D
	<b>Unit</b> <small>lbs Kg</small>	11.0 lbs 5.0 Kg	11.0 lbs 5.0 Kg	11.0 lbs 5.0 Kg	9.7 lbs 4.4 Kg	9.7 lbs 4.4 Kg	4.0 lbs 1.8 Kg
	<b>Sealing Gun</b> <small>lbs Kg</small>	N/A	0.5 lbs 0.2 Kg	0.5 lbs 0.2 Kg	N/A	0.5 lbs 0.2 Kg	0.5 lbs 0.2 Kg
<b>Power Type</b>	A/C	A/C	Battery Operated	A/C	A/C	Battery Operated	
<b>Power Source</b>	100-240 V 50/60 Hz	100-240 V 50/60 Hz	12V / 10AH NiMH Battery (rechargeable)	100-240 V 50/60 Hz	100-240 V 50/60 Hz	12V / 4.5AH NiMH Battery (rechargeable)	
<b>Max Tubing Dia.</b>	6 mm (1/4")	6 mm (1/4")	6 mm (1/4")	6 mm (1/4")	6 mm (1/4")	6 mm (1/4")	
<b>Remarks</b>	—	—	—	 <p>The 530 &amp; 540 sealers can be used stand alone or linked as a multi-head sealing unit. <b>Link 3, 4, 5, 6 or more units together</b> (High Volume Use)</p>		*Approved for use during a standard donation or apheresis procedure.	

\*All devices are CE and UL compliant.

**CORPORATE HEADQUARTERS:**  
65 Commerce Way  
Hackensack, NJ 07601  
TEL: 201-708-1400  
TEL: 866-71-BLOOD  
FAX: 201-708-1104  
info@GenesisBPS.com

**INTERNATIONAL:**  
Genesis BPS International Sàrl  
CP 2361, 1260 Nyon 2, Switzerland  
international@GenesisBPS.com

www.GenesisBPS.com

# GENESIS BPS™

Technology is in our Blood.™